



Cell Jet

- High Capacity Spray System
- Compressed Air Blow-off with Optional High Volume Heated Pressure Blow-off
- Variable Speed Table Drive
- Common Point Load & Unload
- Automatic Vertical Door
- Robot Load/Unload (Optional)
- Solution Filtration
- Stainless Steel Construction
- Small Foot-Print

Cell-U-Clean - Series Cell Jet

All specifications are subject to change without notice



CLEANING TECHNOLOGIES GROUP

RANSOHOFF BLACKSTONE-NEY ULTRASONICS CTG ASIA

MODEL NUMBER	CELL JET
Production Rate	60 Second Cycle
WORKING ENVELOPE (DIA x H)	36" x 24"
WORKING ENVELOPE (DIA x H)	915mm x 610mm
LOAD HEIGHT	36" (990mm)
WASH TANK CAPACITY	180 Gallons (684 Liters)
PART WEIGHT	500 Lbs (227 kg)
CONTROLS	Siemens PLC and HMI
FLOOR SPACE (L x W x H)	8.0' X 5.0' X 9' 0" (2440mm x 1525mm x 2745mm)
UTILITY REQUIREMENTS	460V 3 Ph, 60 Hz

Ransohoff
 (800) 248-9274
 4933 Provident Drive
 Cincinnati, OH 45246
www.ctgclean.com

Blackstone-NEY Ultrasonics
 (800) 766-6606
 P.O. Box 220
 9 N. Main St.
 Jamestown, NY 14702-0220

CTG Asia
 (86)0512-66161698
 56 Songshan Road
 Suzhou New District
 Jiangsu Province, China PRC: 215151